



| SPECIFICATION | CONNECTION | BIPOLAR |
|---|------------|------------|
| AMPS/PHASE | | 1.00 |
| RESISTANCE/PHASE(Ohms)@25°C | | 3.90±10% |
| INDUCTANCE/PHASE(mH)@1KHz | | 2.00±20% |
| HOLDING TORQUE(Nm)[lb-in] | | 0.09[0.80] |
| STEP ANGLE(°) | | 0.90 |
| STEP ACCURACY(NON-ACCUM) | | ±5.00% |
| ROTOR INERTIA(g-cm ²) | | 6 |
| WEIGHT(Kg)[lb] | | — |
| TEMPERATURE RISE:MAX.80°C (MOTOR STANDSTILL;FOR 2PHASE ENERGIZED) | | |
| AMBIENT TEMPERATURE -10°C~50°C[14°F~122°F] | | |
| INSULATION RESISTANCE 100 Mohm (UNDER NORMAL TEMPERATURE AND HUMIDITY) | | |
| INSULATION CLASS B 130°C[266°F] | | |
| DIELECTRIC STRENGTH 500VAC FOR 1MIN.(BETWEEN THE MOTOR COILS AND THE MOTOR CASE) | | |

| TYPE OF CONNECTION (EXTERN) | | MOTOR | |
|-----------------------------|---------|-------|---------|
| PIN NO | BIPOLAR | LEADS | WINDING |
| 1 | A — | RED | |
| 2 | A\ — | GRN | |
| 3 | B — | BLK | |
| 4 | B\ — | BLU | |

| PULLEY SPECIFICATIONS | | |
|-----------------------|----|-----|
| MODULE | m | 0.5 |
| NUMBER OF TEETH | Z | 10 |
| PITCH DIAMETER | d | Ø5 |
| OUTSIDE DIAMETER | da | Ø6 |
| PRESSURE ANGLE | α | 20° |
| MATERIAL | | H59 |

FULL STEP 2 PHASE-Ex. ,
WHEN FACING MOUNTING END (X)

| STEP | A | B | A\ | B\ | | |
|------|---|---|----|----|---|-----|
| 1 | + | + | - | - | ↓ | CCW |
| 2 | - | + | + | - | | |
| 3 | - | - | + | + | ↑ | CW |
| 4 | + | - | - | + | | |

SKYSMotor

| | | |
|-------|-----------|-----------|
| APVD | | 6.28.2021 |
| CHKD | | |
| 1.5:1 | DRN | |
| SCALE | SIGNATURE | DATE |

STEPPER MOTOR

14HR07-1004VRN